

Systems Evaluation and Assessment (SEA) Sub-Element

Common Scenarios and Metrics Requirements


Sandy Lozito
Level 3 Manager
SEA Sub-element







System Evaluation and Assessment Relationship between the Sub elements









System Evaluation and Assessment General Tasks

- Develop scenarios and metrics for evaluation of the SLIC concepts
- Conduct an initial validation assessment of the VAST real-time tools
- Conduct an initial assessment of the selected concepts
- Conduct an initial assessment of the integrated concepts
- Conduct the final evaluation of the integrated concept(s) using the VAST tools







Scenarios/Metrics

- Scenarios and Metrics will be used to help evaluate the concepts from VAMS/System Level Integrated Concepts
 - -Initial evaluation of concepts will be self-evaluation
 - The scenarios/metrics for self-evaluation can be used to assist the SEA scenario/metric development
- There can be many scenarios and metrics, but ultimately they must be applicable for broad evaluations
 - Scenarios addressing multiple airspace domain and concepts addressing more specific domains
 - Scenarios addressing multiple parts of the triad (AOC/ATC/FD)







Scenario Requirements


- Scenarios are necessary for the evaluation of the "capacity-increasing" concepts
- Scenarios must test the concepts' ability to increase capacity and maintain (or increase) safety
- Scenarios must cover all domains (e.g., surface, terminal, enroute)
- Scenarios must consider normal and non-normal events
- Scenarios must cover real-time and fast-time testing
- Scenarios must test all parts of the NAS triad: AOC, ATC, flight deck
- Scenarios must be able to test both single-domain concepts and more broad concepts
- SEA is writing the requirements for the scenarios







Scenario Parameters within SEA





Some Scenario/Metric Parameters

Forecast	Demand	System	Environment	Scope
Economic Activity	Number of Airports	Aircraft Characteristics	Weather	Whole v. part of NAS
Energy Availability	Fleet mix	Airport Characteristics	Safety Situations Operational errors Reduced Landing	Fidelity of the Scenario
War and pestilence	Load factor	Airspace Characteristics	Capacity • Aircraft/Vehicle On the Runway	Temporal Resolution
Environmental Concerns	Schedule	CNS Infrastructure	Failures	Simulation Timing/ Synchronization
Demographics	Origination/ Destination Pair	NAS Architecture	Security Situations	
Travel Confidence		Humans		



Note: Assume a multiple-day schedule of flights for these scenarios





Framework for Scenario & Metrics Development*

Stakeholder Viewpoints (questions to be answered)

Stakeholder Viewpoints (questions to be answered)

output evaluation metrics metrics

concepts

1. Scope:

- •issues
- NAS Domain
- challenges
- assumptions

2. Top Level **Descriptions:**

- core ideas
- functions

3. Detailed Descriptions:

- performance
- roles, responsibilities
- •@ humans & machine
- •human factors
- user interfaces

4. NAS infrastructure & technology impacts:

- transition planning
- architecture
- technology requirements



operational

scenarios

Scenario Elements:

- NAS Domain
- NAS Perturbations
- (e.g. Wx, Security Incidents)
- Origin/Destination Demand Assumed Technologies
- •Human/Machine Performance Defined ATM Procedures
- Assumed Equipage
- •Fleet Mix
- Etc.



NAS Model

Simulations



- ·Safety incidents (proximity to minimum separation, incursions, encroachments, etc.)

Number of traffic events

landings, etc.)

events (requests,

(takeoffs, sector crossings,

Number of communication

clearances, directives, etc.)

throughput (traffic volume)

- •Elapsed flight times
- •Fuel burn

Delay

- Capital investments
- Personnel workloads
- •Etc.

- Average aircraft flight time per air route*
- Average aircraft payload per flight mile
- Operational cost per passenger mile
- Average taxi time from pushback to wheels up during peak traffic periods per specific airports or taxi paths within airports
- Average voice channel occupancy time per departure from pushback to take off
- Average Airport arrival rate during peak periods
- Rate of arrivals per controller hour per airport
- Aircraft (or engine, or other component) maintenance costs per fliaht mile
- •Etc.
- * a defined city pair air route







